

**ATP325x**



## STANDARD EQUIPMENT

220V/380V power supply to the cage

Air breathing line from turntable to the cage

Auto levelling basket

Automatic stabilization

Cage hook (max 400 kg / 882 lbs)

Cage multifunction pin

Cage rotation

Colored LED display on all four control stations

Dead man pedal both on the cage and on turntable controls

Fully electronic proportional hydraulic controls driven by canBUS system

Hands free intercom system ground/cage

Hoist hook on main boom (max 1000 kg / 2205 lbs)

Memory function

Multilanguage display messages

One click auto-closing function

Remote management and diagnostic software

Smooth movements, no flapping with brakes and ramps

Stable aluminium rescue ladder with automatic opening of articulated boom ladder handrail

Telescopic aluminium water line (diameter 100 mm / 4 in)

Ultrasonic anti collision system for cage and cab protection

Variable outreach management

Water sprinkler for cage protection

Wheelchair easy inlet on the cage

## STANDARD COMPLIANCE

UNI EN 1777





UNI EN 1846

CE (european certification)





## PERFORMANCES

	<i>metric</i>	<i>US</i>
Working height	32,5 m	106 ft 7 in
Horizontal outreach	24 m	78 ft 9 in
Up and over clearance	25 m	82 ft
Downreach	- 5 m	-16 ft 5 in
 Lift capacity	400 kg	882 lbs
 Minimum GVW	18 T	39683 lbs
 Water capacity	3800 l/min	1004 GPM (US liquid)
 Operating wind speed	14 m/s	46 fps

## MEASUREMENTS

	<i>metric</i>	<i>US</i>
Foldable front platform on the cage	1360x520 mm	4 ft 5 in x 1 ft 9 in
<b>A</b> Rescue cage size	2000x1000x1100 mm	6 ft 7 in x 3 ft 4 in x 3 ft 7 in
<b>B</b> Height*	3850 mm	12 ft 8 in
<b>C</b> Length*	9950 mm	32 ft 8 in
<b>D<sub>1</sub></b> Width* outriggers in	2500 mm	8 ft 3 in
<b>D</b> Width* outriggers out	6000 mm	19 ft 8 in
<b>E</b> Departure angle* (minimum)	12°	22%

\* Depending on chassis

