

**ALP375x**



**ALP1230x**

## STANDARD EQUIPMENT

- 220V/380V power supply to the cage
- Air breathing line from turntable to the cage
- Auto levelling basket
- Automatic stabilization
- Cage hook (max 500 kg / 1102 lbs)
- Cage multifunction pin
- Cage rotation
- Colored LED display on all four control stations
- Dead man pedal both on the cage and on turntable controls
- Fully electronic proportional hydraulic controls driven by canBUS system
- Hands free intercom system ground/cage
- Hoist hook on main boom (max 2000 kg / 4409 lbs)
- Memory function
- Multilanguage display messages
- One click auto-closing function
- Remote management and diagnostic software
- Smooth movements, no flapping with brakes and ramps
- Stable aluminium rescue ladder with automatic opening of articulated boom ladder handrail
- Telescopic aluminium water line (diameter 100 mm / 4 in)
- Ultrasonic anti collision system for cage and cab protection
- Variable outreach management
- Water sprinkler for cage protection
- Wheelchair easy inlet on the cage

## STANDARD COMPLIANCE

- UNI EN 1777
- UNI EN 1846
- CE (european certification)



ALP1230x

## PERFORMANCES

	<i>metric</i>	<i>US</i>
Working height	37,5 m	123 ft
Horizontal outreach	24 m	78 ft 9 in
Up and over clearance	30 m	98 ft 5 in
Downreach	- 5 m	-16 ft 5 in
Lift capacity	500 kg	1102 lbs
Minimum GVW	26 T	57320 lbs
Water capacity	3800 l/min	1004 GPM (US liquid)
Operating wind speed	14 m/s	46 fps

## MEASUREMENTS

	<i>metric</i>	<i>US</i>
Foldable front platform on the cage	1360x520 mm	4 ft 5 in x 1 ft 9 in
<b>A</b> Rescue cage size	2000x1000x1100 mm	6 ft 7 in x 3 ft 4 in x 3 ft 7 in
<b>B</b> Height*	3850 mm	12 ft 8 in
<b>C</b> Length*	10250 mm	33 ft 7 in
<b>D<sub>1</sub></b> Width* outriggers in	2500 mm	8 ft 3 in
<b>D</b> Width* outriggers out	5500 mm	18 ft
<b>E</b> Departure angle* (minimum)	12°	22%

\* Depending on chassis



